

*Ramset collated Gas Tool Fasteners are specifically engineered for optimal performance in Ramset Gas Power Tools using fastener magazines*

## TRAKFAST STANDARD FUEL/PIN PACK

*For high volume, repetitive fastenings to concrete and steel such as drywall track to concrete*

1000 PINS AND 1 FUEL CELL PER BOX.



PART NUMBER	PIN LENGTH		DESCRIPTION	TF1100
	Inches	(mm)		
FPP012	1/2	(12.7)	1/2" Plated steel pin	■
FPP034B	3/4	(19.1)	3/4" Black pin	■
FPP100	1	(25.4)	1" Plated pin	■
FPP114	1-1/4	(31.8)	1-1/4" Plated pin	■

Shank diameter = .109 Head diameter = .250

## TRAKFAST STEP SHANK/ FUEL PIN PACK

*For high volume, repetitive fastenings to hard concrete and hard steel such as drywall track to hard concrete and steel*

1000 PINS AND 1 FUEL CELL PER BOX.



PART NUMBER	PIN LENGTH		DESCRIPTION	TF1100
	Inches	(mm)		
FPP012S	1/2	(12.7)	1/2" Plated step shank pin	■
FPP034S	3/4	(19.1)	3/4" Plated step shank pin	■

Shank diameter = .104/.118 Head diameter = .250

## TRAKFAST BREAKAWAY STRIP FUEL/PIN PACK

*For high volume, repetitive fastenings to concrete such as wood furring to concrete*

1000 PINS AND 1 FUEL CELL PER BOX.  
COLLATION DESIGNED TO BREAKAWAY ON IMPACT.



PART NUMBER	PIN LENGTH		DESCRIPTION	TF1100
	Inches	(mm)		
FPP034T	3/4	(19.1)	3/4" Plated pin	■
FPP100T	1	(25.4)	1" Plated pin	■
FPP114T	1-1/4	(31.8)	1-1/4" Plated pin	■
FPP112T	1-1/2	(38.1)	1-12" Plated pin	■

Shank diameter = .109 Head diameter = .250

## T3MAG FUEL/PIN PACK

*Larger .125 shank diameter offers improved success rate (15 pin strip)*

1000 PINS AND 1 FUEL CELL PER BOX



PART NUMBER	PIN LENGTH		DESCRIPTION	T3MAG
	Inches	(mm)		
T3012	1/2	(12.7)	1/2" steel pin with T3 fuel cell	■
T3012S	1/2	(12.7)	1/2" premium steel pin with T3 fuel cell	■
T3034B	3/4	(19.1)	3/4" concrete pin with T3 fuel cell	■
T3034S*	3/4	(19.1)	3/4" step shank pin with T3 fuel cell	■
T3100	1	(25.4)	1" concrete pin with T3 fuel cell	■

Shank diameter = .125 \*Shank diameter = .104/.125

Head diameter = .250

## PLY138—TRAKFAST PLYWOOD PIN

*For attaching plywood to metal studs*

1000 PINS AND 1 FUEL CELL PER BOX.

### SPECIFICATIONS

- Fastener Length: 1-3/8"
- Shank Diameter: .100 dia. (before knurl)
- Head Diameter: .250
- Helical Knurled Shank
- Mechanical Zinc Plated

### Can Be Used With:

Wood Sheathings: 3/8", 1/2", 5/8", 3/4"  
Steel Stud Gauges: 16, 18, 20  
(also works well in 12 and 14 gage)

